




SKF BEARING MANUFACTURING CO.,LTD.



30 mm x 72 mm x 19 mm KOYO TRA0607R tapered roller bearings

Bearing No. TRA0607R

TRA0607R Bearing 2D drawings and 3D CAD models

Size	30x72x20.75 mm
Bore Diameter	30 mm
Outer Diameter	72 mm
Width	20,75 mm
d	30 mm
D	72 mm
T	20,75 mm
B	19 mm
C	14 mm
a	18,6 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	38,5 mm
da max	39 mm
Da min	58 mm
Da max.	63,5 mm
Db min.	68 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,405 Kg
Basic dynamic load rating (C)	56,9 kN
Basic static load rating (C0)	55,6 kN
(Grease) Lubrication Speed	5900 r/min
(Oil) Lubrication Speed	7900 r/min
Calculation factor (e)	0,55



SKF BEARING MANUFACTURING CO.,LTD.

Calculation factor (Y0)	0,6
Bearing No.	TRA0607R
r(min)	1.5
r1(min)	1.5
Cr	71.2
C0r	55.6
Cu	8.10
Grease lub.	5900
Oil lub.	7900
a	18.6 mm
da(min)	38.5
db(max)	39
Da(max)	63.5
Da(min)	58
Db(min)	68
Sa(min)	3
Sb(min)	4.5
ra(max)	1.5
rb(max)	1.5
e	0.55
Y1	1.10
Y0	0.60
(Refer.) Mass(kg)	0.405